BKPv 8470

ProfiLine

Total gross capacity	856 litre
Ext. dimensions in mm (w/d/h)	790/980/2150
Int. dimensions in mm (w/d/h)	623/800/1550
Energy consumption in 24 h	1,474 kWh
Climate rating[1]	T 5
Cooling system	forced-air
Defrosting	automatic
Temperature range	-5°C to +15°C
Gastronorm	600x800 mm
Housing material/colour	stainless steel/stainless steel
Door/lid material	Stainless steel
Liner Material	304-grade stainless steel
Type of control	electronic controller
Temperature display	external digital
Interior light	–
Fault: warning signal	visual and audible
Interface	–
volt-free alarm contact	yes
Shelves	25
Adjustable Shelving	25
Number of drawers	–
Number of baskets	–
Maximum number of baskets	–
Shelf material	stainless steel L-shapes trayslides
Shelf loading	–
Height of adjustable legs	120-170
Castors/type of castors	–
Door handle	full-length integrated door handle
Foot pedal opener	–
Self-closing door	yes
Insulation	83 - 60 mm
Defrost water drain	–
Refrigerant	R 290
Noise level	58 dB(A)
Gross/net weight	181/162 kg
EAN-Nr.	9005382167731

Subject to modification. Timestamp: 20.03.2015

1 Climate Ratings: **SN** +10°C to +32°C **N** +16°C to +32°C **ST** +16°C to +38°C **T** +16°C to +43°C

LIEBHERR